

of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx EPS 19.0021X

Issue No: 0

Page 1 of 4

Certificate history:

IS

Issue No. 0 (2019-09-13)

Status:

Current

Date of Issue:

2019-09-13

Applicant:

Maico Elektroapparate-Fabrik GmbH

Steinbeisstraße 20

78056 Villingen-Schwenningen

Germany

Equipment:

Alternating current motor types EZQ 20/4-E Ex e and fan type EZQ 20/4-E Ex e; EZS

20/4-E Ex e and fan type EZS 20/4-E Ex e

Optional accessory:

Type of Protection:

increased safety "e"; protection by enclosure "t", non-electrical equipment "h"

Marking:

Ex eb IIB+H₂ T3 Gb

 $\operatorname{Ex}\operatorname{h}\operatorname{IIB+H}_{2}\operatorname{T3}\operatorname{Gb}$

Ex tb IIIB T200°C Db IP64

Ex h IIIB T200°C Db

Approved for issue on behalf of the IECEx

Certification Body:

Position:

Signature:


(for printed version)

Date:

Holger Schaffer

Manager certification

2019-09-13



 ${\bf 2. \ This \ certificate \ is \ not \ transferable \ and \ remains \ the \ property \ of \ the \ issuing \ body.}$

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Bureau Veritas Consumer Products Services Germany GmbH Businesspark A96 86842 Türkheim Germany





of Conformity

Certificate No: IECEx EPS 19.0021X Issue No: 0

Date of Issue: **2019-09-13** Page 2 of 4

Manufacturer: Maico Elektroapparate-Fabrik GmbH

Steinbeisstraße 20

78056 Villingen-Schwenningen

Germany

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-31 : 2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

IEC 60079-7: 2017 Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

Edition:5.1

ISO 80079-36: 2016 Explosive atmospheres - Part 36: Non-electrical equipment for explosive atmospheres - Basic methods and

Edition:1.0 requirements

ISO 80079-37: 2016 Explosive atmospheres - Part 37: Non-electrical equipment for explosive atmospheres - Non electrical type

Edition:1.0 of protection constructional safety "c", control of ignition source "b", liquid immersion "k"

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the

Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

DE/EPS/ExTR19.0020/00

Quality Assessment Report:

DE/PTZ/QAR18.0003/00



IECEx Certificate of Conformity

Certificate No:	IECEx EPS 19.0021X	Issue No: 0
Date of Issue:	2019-09-13	Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The fan is used for ventilation of commercially used rooms (dyeing room, battery room, commercial space, production facility, etc.) with a potentially explosive atmosphere.

Electrical data:

See user manual.

Model code:

See annex.

SPECIFIC CONDITIONS OF USE: YES as shown below:

The fan shall be operated only with the rated voltage as indicated on the name plate.

The fan shall only be operated during free intake or blow-out, if the impeller is protected against contact in accordance with ISO 13857. Use the safety guard SG....

Speed control is not allowed.

For securing the EZQ / EZS-Ex e devices a motor circuit breaker is mandatory.

Never run several fans in parallel on a single thermistor triggering system.

Make sure there is sufficient air gap between impeller and housing.

Operate the fan only within the permissible ambient and operating conditions and operating temperature.

Provide a free air inlet or outlet with a protection device according to IEC 60529. A Double-sided protection is mandatory. The device and pipelines must be secured against the ingress of foreign objects.

Ensure a sufficient air flow supply. Operate the fan in the permitted air flow range.

Operation with frequency converter is not permitted.

Do not put any objects in the device.

Ensure degree of protection by proper insertion of the cables into the terminal box.

The assembly and installation must meet the requirements of IEC 60079-14.

The no-load operation don't have practical meaning, because of the engine shall be operated only in the fan as intended.

The allowed voltages are according to the manual.

Only motor circuit breaker with a type examination certificate in accordance with IECEx and a marking in accordance with IECEx (Gb/Db) are permitted or compatible requirements acc. the IECEx –Scheme. The motor circuit breaker must be set to the rated motor current (not I_{max}).



IECEx Certificate of Conformity

Certificate No:

IECEx EPS 19.0021X

Issue No: 0

Date of Issue:

2019-09-13

Page 4 of 4

Annex:

Attachment to IECEx certificate IECEx EPS 19.0021X.pdf



Attachment to certificate

IECEx EPS 19.0021X



Applicant:

Maico Elektroapparate-Fabrik GmbH

Steinbeisstraße 20

78056 Villingen-Schwenningen

Germany

Electrical Apparatus:

Alternating current motor

EZQ 20/4-E Ex e and fan type EZQ 20/4-E Ex e, EZS 20/4-E Ex e and fan type EZS 20/4-E Ex e

Type code for EZ-/DZ-Fans

Designation e.g.: DZQ 35/4 Ex e

D/E	Z	Q/R/S/D	35	/	4	Exe
1	2	3	4		5	6

No	Designation	Meaning
1	D	Three-phase AC
1	E	Single-phase AC
2	Z	"Zephir" impeller
3	D	Roof fan
3	R	Duct sleeve
,	S	Steel wall ring
	Q	Square wall plate
4	35	Nominal Diameter of the nozzle in cm (20, 25, 30, 35, 40, 45, 50, 60)
5	4	Number of poles of the motor (2-6)
6	Exe	Explosion proof