DAR 63/4 1,1





Short description

Axial duct fan, DN 630, three-phase AC, nominal power 1.1 kW

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0121

Technical data

Air flow volume	15.084 m³/h			
Rotating speed	1.440 1/min			
Impeller type	axial			
Speed controllable	✓			
Reversing capacity	-			
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	1.100 W			
I _{nom}	2,5 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal / Vertical			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	43 kg			
Weight including packaging	48 kg			
Nominal size	630 mm			
Width	730 mm			
Height	500 mm			
Depth	730 mm			
Width with packaging	830 mm			
Height with packaging	600 mm			
Depth with packaging	830 mm			
Airstream temperature at I _{Max}	-10 °C up to 50 °C			
PTC DIN 44082	M 100			



DAR 63/4 1,1

Packing unit	1 piece
Range	C
GTIN (EAN)	4012799731214

Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	44,5 %				
Measurement category	С				
Efficiency category	static				
Efficiency level N	50,5				
VSD necessary	No				
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration				
place of establishment	court, HRB 601233 / Villingen-Schwenningen				
Art. No.	0073.0121				
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}	1,093 kW / 9.425 m³/h / 185,7 Pa				
n _{BEP}	1.420 1/min				
Specific ratio	≈ 1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
Objects used to measure efficiency which are not described by the	-				
measurement category					
I _{BEP}	2,5 A				
Sound power levelL _{WA7}	82 dB(A)				

Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total	
L _{WA5} , S5	57	64	69	74	77	76	75	69	82	
(dB(A))										

L_{WA5}= free inlet sound power level in dB.

DAR 63/4 1,1



Characteristic curve



Dimensioned drawing [mm]

