DAR 80/4 5,5





Short description

Axial duct fan, DN 800, three-phase AC, nominal power 5.5 \mbox{kW}

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0142

Technical data

L At- Manual Control	04 500 22/			
Air flow volume	31.500 m³/h			
Rotating speed	1.440 1/min			
Impeller type	axial			
Speed controllable	√ -			
Reversing capacity				
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	5.500 W			
I _{nom}	10,74 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	90 kg			
Weight including packaging	125 kg			
Nominal size	800 mm			
Width	910 mm			
Height	590 mm			
Depth	910 mm			
Width with packaging	1.140 mm			
Height with packaging	740 mm			
Depth with packaging	1.140 mm			
Airstream temperature at I _{Max}	-10 °C up to 50 °C			
PTC DIN 44082	M 100			



DAR 80/4 5,5

Packing unit	1 piece
Range	C
GTIN (EAN)	4012799731429

Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	43,4 %			
Measurement category	С			
Efficiency category	static			
Efficiency level N	45,2 No			
VSD necessary				
Year of manufacture	see rating plate			
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration			
place of establishment	court, HRB 601233 / Villingen-Schwenningen			
Art. No.	0073.0142 5,188 kW / 21.902 m³/h / 370,2 Pa			
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}				
n _{BEP}	1.470 1/min			
Specific ratio	≈ 1			
Information about dismantling and disposal	see mounting instructions			
Information about installation, operation and repairs	see mounting instructions			
Objects used to measure efficiency which are not described by the	-			
measurement category				
I _{BEP}	10,74 A			
Sound power levelL _{WA7}	92 dB(A)			

Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA5} , S5	64	75	83	85	86	86	85	79	92
(dB(A))									

L_{WA5}= free inlet sound power level in dB.

DAR 80/4 5,5



Characteristic curve



Dimensioned drawing [mm]

