DAR 80/6 0,55





Short description

Axial duct fan, DN 800, three-phase AC, nominal power 0.55 kW, 6-pin

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0143

Technical data

Lace	1 40 500 20			
Air flow volume	16.596 m³/h			
Rotating speed	960 1/min			
Impeller type	axial			
Speed controllable	✓			
Reversing capacity	-			
Type of voltage	Three-phase AC			
Rated voltage	400 V			
Frequency	50 Hz			
Nominal output	550 W			
I _{nom}	1,71 A			
Degree of protection	IP 55			
Insulation class	F			
Pole-changeable	-			
Installation site	Duct			
Installation position	Horizontal			
Housing material	Sheet steel with epoxy coating			
Impeller material	Polyamide			
Colour	grey			
Weight	68 kg			
Weight including packaging	84 kg			
Nominal size	800 mm			
Width	910 mm			
Height	590 mm			
Depth	910 mm			
Width with packaging	1.140 mm			
Height with packaging	740 mm			
Depth with packaging	1.140 mm			
Airstream temperature at I _{Max}	-10 °C up to 50 °C			
PTC DIN 44082	M 100			



DAR 80/6 0,55

Packing unit	1 piece
Range	С
GTIN (EAN)	4012799731436

Technical data according to ErP in Best Efficiency Point (BEP)

Total efficiency η	41,8 %				
Measurement category	C static 48,6 No				
Efficiency category					
Efficiency level N					
VSD necessary					
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration court, HRB 601233 / Villingen-Schwenningen 0073.0143 0,833 kW / 9.648 m³/h / 130 Pa 950 1/min				
place of establishment					
Art. No.					
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}					
n _{BEP}					
Specific ratio	≈ 1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
Objects used to measure efficiency which are not described by the	-				
measurement category					
I _{BEP}	1,71 A				
Sound power levelL _{WA7}	89 dB(A)				

Sound power level in octave range


	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total	
L _{WA5} , S5	56	68	82	85	82	78	76	69	89	
(dB(A))										

L_{WA5}= free inlet sound power level in dB.

DAR 80/6 0,55



Characteristic curve



Dimensioned drawing [mm]

