DZF 35/4 BH





Short description

Airotherm three-phase AC modular system for air heating

Application examples

Office, Restaurant, Fitness room, Workplace, Showroom

Article number 0085.0031

Technical data

Air flow volume	1.100 m³/h				
Rotating speed	1.400 1/min				
Rated voltage	400 V				
Frequency	50 Hz				
Power consumption	160 W				
I _{nom}	0,35 A				
I _{max}	0,35 A				
Degree of protection	IP 55				
Pole-changeable	_				
Mains cable	5 x 1,5 mm²				
Installation site	Wall				
Type of installation	Recessed-mounted				
Installation position	horizontal				
Housing material	Sheet steel, galvanised				
Weight	8,2				
Weight including packaging	8,12 kg				
Nominal size	350 mm				
Width with packaging	440 mm				
Height with packaging	340 mm				
Depth with packaging	440 mm				
Packing unit	1 piece				
Range	С				
GTIN (EAN)	4012799850311				

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA8} , high	-	-	-	-	-	_	-	_	67
(dB(A))									

DZF 35/4 BH



 L_{WA8} = housing and free outlet sound power level in dB.

Dimensioned drawing [mm]

