

DZF 35/6 BH



Short description

Airotherm three-phase AC modular system for air heating

Application examples

Office, Restaurant, Fitness room, Workplace, Showroom

Article number 0085.0030

Technical data

Air flow volume	650 m³/h
Rotating speed	900 1/min
Rated voltage	400 V
Frequency	50 Hz
Power consumption	85 W
I _{nom}	0,2 A
I _{max}	0,2 A
Degree of protection	IP 55
Pole-changeable	–
Mains cable	5 x 1,5 mm²
Installation site	Wall
Type of installation	Recessed-mounted
Installation position	horizontal
Housing material	Sheet steel, galvanised
Weight	8
Weight including packaging	8,1 kg
Nominal size	350 mm
Width with packaging	440 mm
Height with packaging	340 mm
Depth with packaging	440 mm
Packing unit	1 piece
Range	C
GTIN (EAN)	4012799850304

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA8, high} (dB(A))	–	–	–	–	–	–	–	–	55

DZF 35/6 BH

L_{WA8} = housing and free outlet sound power level in dB.

Dimensioned drawing [mm]

