

ER-AP 60



Short description

Surface-mounted fan for air extraction, air volume 61 m³/h

Application examples

Bathroom, Kitchen, Multiple family unit, Day room, Dining room

Article number 0084.0150

Technical data

Model	Standard model
Air flow volume	61 m ³ /h
Rotating speed	1.250 1/min
Air direction	Air extraction
Speed controllable	-
SEC average	-3,87 kWh/(m ² *a)
Rated voltage	230 V
Frequency	50 Hz
Power consumption	21 W
I _{max}	0,17 A
Degree of protection	IP X5
Mains cable	3 / 1,5 mm ²
Installation site	Wall / Ceiling
Type of installation	Surface-mounted
System type	Decentralised
Material	Synthetic material
Colour	Traffic white, similar to RAL 9016
Weight	1,9 kg
Filter class	G2
Fire protection	No
Connection diameter	75 mm / 80 mm
Width	236 mm
Height	236 mm
Depth	217,5 mm
Airstream temperature at I _{Max}	40 °C
Sound pressure level	40 dB(A) (Specifications in accordance with DIN 18017-3 at an equivalent absorption area A _L = 10 m. ²)
Approval number	Z-51.1-42
Packing unit	1 piece

ER-AP 60


Range	B
GTIN (EAN)	4012799841500

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L_{WA7, high} (dB(A))	-	-	-	-	-	-	-	-	43

L_{WA7}= housing and free inlet sound power level in dB.

Characteristic curve



ER-AP 60

Dimensioned drawing [mm]

