# **ERK 100**





### Short description

Diagonal fan for duct installation, DN 100, one-level

## Application examples

Production site, Storage facility, Day room, Showroom, Workshop

Article number 0080.0173

#### Technical data

| Model                      | Standard model        |  |  |  |  |
|----------------------------|-----------------------|--|--|--|--|
| Air flow volume            | 130 m³/h              |  |  |  |  |
| Rotating speed             | 2.200 1/min           |  |  |  |  |
| Impeller type              | diagonal              |  |  |  |  |
| Speed controllable         | 1                     |  |  |  |  |
| Reversing capacity         | -                     |  |  |  |  |
| Rated voltage              | 230 V                 |  |  |  |  |
| Frequency                  | 50 Hz                 |  |  |  |  |
| Nominal output             | 25 W                  |  |  |  |  |
| Power consumption          | 25 W                  |  |  |  |  |
| I <sub>max</sub>           | 0,16 A                |  |  |  |  |
| Degree of protection       | IP 44                 |  |  |  |  |
| Insulation class           | В                     |  |  |  |  |
| Installation position      | vertical / horizontal |  |  |  |  |
| Housing material           | Polypropylene         |  |  |  |  |
| Weight                     | 1 kg                  |  |  |  |  |
| Weight including packaging | 1,28 kg               |  |  |  |  |
| Nominal size               | 100 mm                |  |  |  |  |
| Width                      | 171 mm                |  |  |  |  |
| Height                     | 196 mm                |  |  |  |  |
| Depth                      | 238 mm                |  |  |  |  |
| Width with packaging       | 208 mm                |  |  |  |  |
| Height with packaging      | 199 mm                |  |  |  |  |
| Depth with packaging       | 245 mm                |  |  |  |  |
| Airstream temperature      | 40 °C                 |  |  |  |  |
| Packing unit               | 1 piece               |  |  |  |  |
| Range                      | С                     |  |  |  |  |
| GTIN (EAN)                 | 4012799801733         |  |  |  |  |

# **ERK 100**




### Sound power level in octave range

|                         | 63 Hz | 125 Hz | 250 Hz | 500 Hz | 1 kHz | 2 kHz | 4 kHz | 8 kHz | Total |  |
|-------------------------|-------|--------|--------|--------|-------|-------|-------|-------|-------|--|
| L <sub>WA5</sub> , high | -     | 40     | 43     | 42     | 40    | 36    | 34    | 26    | 45    |  |
| (dB(A))                 |       |        |        |        |       |       |       |       |       |  |

L<sub>WA5</sub>= free inlet sound power level in dB.

#### Characteristic curve



### Dimensioned drawing [mm]

