RSR 20-1





Short description

Flexible tubular sound absorber with lip seal, 25 mm sound absorbing cover, length 1000 mm, DN 200

Application examples

Showroom, Restaurant, Theatre, Production site, Industrial building

Article number 0092.0597


Technical data

| Model | 25 mm sound absorbing cover |
|----------------------------|-----------------------------|
| Installation site | Fans |
| Material | Aluminium |
| Colour | Silver |
| Weight | 1,5 kg |
| Weight including packaging | 2,12 kg |
| Connection diameter | 200 mm |
| Suitable for nominal size | 200 mm |
| Width | 260 mm |
| Height | 260 mm |
| Depth | 1.000 mm |
| Width with packaging | 265 mm |
| Height with packaging | 265 mm |
| Depth with packaging | 1.175 mm |
| Insertion loss at 63 Hz | 2 dB |
| Insertion loss at 125 Hz | 2 dB |
| Insertion loss at 250 Hz | 4 dB |
| Insertion loss at 500 Hz | 9 dB |
| Insertion loss at 1 kHz | 21 dB |
| Insertion loss at 2 kHz | 28 dB |
| Insertion loss at 4 kHz | 12 dB |
| Insertion loss at 8 kHz | 13 dB |
| Total insertion loss | |
| Insertion loss note | |
| Sound insulation | yes |
| Packing unit | 1 piece |
| Range | С |
| GTIN (EAN) | 4012799925972 |

RSR 20-1



Characteristic curve



Dimensioned drawing [mm]

